

DEKTITE® PREMIUM™

**More flexible sizing
for better coverage...**

CHECK OUT THE BENEFITS!

- Square base will cover a larger opening
Conforms with and follows all roof profiles
- Fewer sizes to stock
- Wider cone sizes means each Dektite will cover
a larger range of penetration diameters
- Paintable with 100% High Gloss Acrylic Paint
- Suitable for Flues and Chimneys
Handles temperatures from -50°C (-112°F) to
115°C (239°F) & up to 150°C (302°F) intermittently
- Twenty year warranty
Just fit it and forget it – we've got you covered



FS 52067
QUALITY ISO9001
AS/NZS 4347



DEKTITE® PREMIUM™

Installation Information



1
Trim the cone to suit pipe size using sharp tin snips.
"When piercing the tip of the cone of DFE 0-35, with a pen or pencil, a wire of up to 8 mm can be pushed through".



2
Slide down pipe using water as a lubricant.



3
Apply sealant by turning back flexible flange.



4
Press base to the roof profile by hand. Smooth out any awkward creases. Don't fully extend to allow for vibration.



5
Fasten using self-sealing fasteners or pop (sealed) rivets.



A Dektite® may be fitted on the 'diamond' for enlarged holes and penetrations on steep pitched roofs up to 45° or deep corrugations.

EASY SELECTION GUIDE

PART #	PIPE INCHES	DESCRIPTION	BASE INCHES	PACK/CTN
C12-0112	1/4" - 2-1/2"	# 1 Premium Dektite	5.5" x 5.5"	15
C12-0113	1/4" - 3"	# 2 Premium Dektite	7" x 7"	15
C12-0114	1/4" - 5"	# 3 Premium Dektite	8.75" x 8.75"	15
C12-0115	3" - 7"	# 4 Premium Dektite	11" x 11"	10
DC12-0116	4" - 8"	# 5 Premium Dektite	12.25" x 12.25"	10
C12-0117	5" - 9"	# 6 Premium Dektite	14.25" x 14.25"	10
C12-0120	6" - 12"	# 7 Premium Dektite	18" x 18"	10
C12-0122	6-3/4" - 14"	# 8 Premium Dektite	19.5" x 19.5"	5
C12-0124	9" - 20"	# 9 Premium Dektite	26.75" x 26.75"	5
C12-0126	15" - 24"	# 10 Premium Dektite		1

Black (EPDM)*
Stadard STOCK
Grey (EPDM)*
Red Silicone

Available in Black and Grey EPDM or Red Silicone

EPDM will withstand constant temperatures at the roof line of -50°C (-122°F) to 115°C (239°F) & up to 150°C (302°F) intermittently.

Red Silicone will withstand constant temperatures at the roof line of -50°C (-112°F) to 200°C (392°F) & up to 250°C (482°F) intermittently.

For higher temperatures always use the Dektite® Silicone range.
Go to www.marathondrains.com for more information on the full range.

FEATURES



Need to flash a tiled roof? Contact Marathon Roofing Products to discuss the tile roof flashing range.