

DEKTITE[®] RETORFIT[™]

When it has to flash around, not over...

CHECK OUT THE BENEFITS!

- **Fast & efficient installation**
Wraps around existing or difficult to access pipes
- **Snaps together in seconds**
The built-in crimp means no loose clips or rivets
- **Grips tight and stays tight**
Made from quality polymer compound
- **Our base makes easy work**
Aluminum base conforms to roof with ease
- **Twenty year warranty**
Just fit it and forget it – we've got you covered



FS 52067
QUALITY ISO9001
AS/NZS 4347



DEKTITE® RETROFIT™

Installation Information

EASY SELECTION GUIDE



1 Trim cone to suit pipe size using tin snips.



2 With clip in downstream position, wrap top of cone around pipe and engage metal teeth in opposing pockets starting at the top.



3 To assist locating clip into pocket, place hand behind seam. Fasten clip with pliers or multitools, working from top to base. Do not over crimp.



4 Apply sealant to underside of Dektite® base and shape to roof by hand.



5 Fasten flashing down and secure clip by placing a fastener either side of clip first.



6 Apply sealant to top of crimp closure and any other potential leak areas.

Code No	Pipe mm	Pipe inch	Base mm	Pitch	Base inches
RF 801	20-70	2"	160	0-40° or	6"
RF 802	50-190	2 - 7"	273	0-40° or	10 ¾"
RF 803	85-255	3 - 10"	369	0-40° or	14 ½"
RFS 4	235-425	9 - 16"	762 x 680	0-40° or	30 x 26 ¾"

Black (EPDM)*
Grey (EPDM)*

Code No	Pipe mm	Pipe inch	Base mm	Pitch	Base inches
RF 901	20-70	2"	160	0-40° or	6"
RF 902	50-190	2 - 7"	273	0-40° or	10 ¾"
RF 903	85-255	3 - 10"	369	0-40° or	14 ½"
RFS24	235-425	9 - 16"	762 x 680	0-40° or	30 x 26 ¾"

Red Silicone

Available in Black and Grey EPDM or Red Silicone

EPDM will withstand constant temperatures at the roof line of -50°C (-122°F) to 115°C (239°F) & up to 150°C (302°F) intermittently.

Red Silicone will withstand constant temperatures at the roof line of -50°C (-112°F) to 200°C (392°F) & up to 250°C (482°F) intermittently.

For higher temperatures always use the Dektite® Silicone range. Go to www.marathondrains.com for more information on the full range.



Need to flash a square penetration? Contact Marathon Roofing Products to discuss the square flashing range.