

ROOFNEK ROOFSAFE

A SIMPLE WATERTITE SOLUTION TO ROOF PENETRATION PROBLEMS

FEATURES:

- Watertite conduit system
- Easily flashed with roof membrane systems
- Aluminum base standpipe
- Solvent welded PVC hooded outlet
- 3 cable openings plus 3 additional knockouts

Roofnek virtually eliminates the need for penetration pockets when flashing/waterproofing flexible roof penetrations. The simple, two-piece construction eliminates time consuming and costly field flashing of electrical cables and wires, and refrigerant conduits.

Dimensions:	Inches	mm
Overall Height	22 3/4	578
Flange Diameter	11 3/4	298
Opening Above Deck	20 3/4	527
Flashing Width	4	102

ELIMINATES CALL-BACKS!

How often have you completed the flashing of a conventional roof and left the jobsite, only to be called back later by the owner or general contractor reporting a roof leak?

You know the cone was properly flashed but did another tradesman properly seal the top? Roofnek eliminates this inconvenience by creating a simple, watertight system that requires no further sealing. It also eliminates the cost of the call-back; when you finish the job you leave the site, confident that you'll not be called back for an open cone leak.

WARNING
Cancer and Reproductive Harm
www.P65Warnings.ca.gov

PVC Coating
Only



3 cable openings plus 3 additional knockouts