



ROOFNEK ROOFSAFE

**A SIMPLE WATERTITE SOLUTION
TO ROOF PENETRATION PROBLEMS**

FEATURES

- *Watertite conduit system*
- *Easily flashed with roof membrane systems*
- *Aluminum base standpipe*
- *Solvent welded PVC hooded outlet*
- *3 cable openings plus 3 additional knockouts*

Roofnek virtually eliminates the need for penetration pockets when flashing/waterproofing flexible roof penetrations. The simple, two-piece construction eliminates time consuming and costly field flashing of electrical cables and wires, and refrigerant conduits.



*SHOWN: 3 cable openings
plus 3 additional knockouts*

Dimensions:	Inches	mm
Overall Height	22 3/4	578
Flange Diameter	11 3/4	298
Opening Above Deck	20 3/4	527
Flashing Width	4	102

Eliminates Call-Backs!

How often have you completed the flashing of a conventional roof and left the jobsite, only to be called back later by the owner or general contractor reporting a roofleak? You know the cone was properly flashed but did another tradesman properly seal the top? Roofnek eliminates this inconvenience by creating a simple, watertight system that requires no further sealing. It also eliminates the cost of the call-back; when you finish the job you leave the site, confident that you'll not be called back for an open cone leak.